



DEV INDUSTRIAL COATINGS

(Manufacturers of Hi-Tech Industrial Paints)

(AN ISO 9001:2008 CERTIFIED COMPANY)

“NAGARJUNA” CHLORINATED RUBBER PAINT

<p>PRODUCT DESCRIPTION</p> <p>RECOMMENDED USE</p>	<p>Nagarjuna” Chlorocoat is single pack air drying chlorinated rubber paint. It provides resistances to salt water ,aliphatic solvents, acid, alkalis and wide range of chemicals</p> <p>Long lasting finished coat in chemicals and fertilizer industry, power plants, breweries,swimming pools, also for marine and industrial environments.</p>
<p>PROPERTIES</p> <p>Finish</p> <p>Shade</p> <p>Standard Coverage</p> <p>Specific Gravity</p> <p>Flash point</p> <p>Touch Dry</p> <p>Surface Dry</p> <p>Hard Dry</p> <p>Scratch hardness(min)</p> <p>DFT</p>	<p>Glossy</p> <p>Any shade as per IS: 5</p> <p>9-10 Sq.Mts/ltr</p> <p>1.0-1.2 Kg/ltr</p> <p>26C</p> <p>30 minutes</p> <p>8 hours</p> <p>12 hours</p> <p>1000grms</p> <p>30 microns</p>
<p>APPLICATIONS SYSTEM</p> <p>Method of Application</p> <p>Compatible Thinner</p> <p>Recoatable Interval</p> <p>Packing</p> <p>Storage Life</p>	<p>Air Spray/Brush</p> <p>“Nagarjuna” Zinc Phos.Primer.</p> <p>24 Hours</p> <p>20 Lts</p> <p>As long as the containers are kept firmly sealed, the contents can be stored up to 6 months without deterioration</p>
<p>Specifications, and data given above represent test results obtained under controlled Conditions. These may vary under actual circumstance</p>	

