



DEV INDUSTRIAL COATINGS

(Manufacturers of Hi-Tech Industrial Paints)

(AN ISO 9001:2008 CERTIFIED COMPANY)

<u>"NAGARJUNA ETCH PRIMER"</u>	
PRODUCT DESCRIPTION	"Nagarjuna" Etch primer is a two component air drying system comprising of base and activator. It has poly vinyl butyral resin along with Zinc tetroxy chrome pigment and conforms to IS 5666-1970. It is also known as wash primer.
RECOMMENDED USE	Each primer is applied on metal surfaces like galvanized steel, aluminium, tin etc. Etch primer gives a very thin adhesive coating for further application of primer or finish paint.
PROPERTIES	
Finish	Matt
Shade	Yellow
Standard Coverage	12-13 sq.mts/lt.
Specific Gravity	0.8 kg/lt.
Touch Dry	15 minutes
DFT	5 microns
APPLICATION SYSTEM	
Mixing Ratio	Base:Activator 1:1 by volume
Method of application	Airless spray /Brush
Compatible Thinner	N.A
Recoat interval	6 hours
Packing	20ltrs
Storage life	As long as the containers are kept firmly sealed, the contents can be stored up to 6 months without deterioration
Specifications, and data given above represent test results obtained under controlled Conditions. These may vary under actual circumstance	

