



DEV INDUSTRIAL COATINGS

(Manufacturers of Hi-Tech Industrial Paints)

(AN ISO 9001:2008 CERTIFIED COMPANY)

"NAGARJUNA" SUPER SYNTHETIC ENAMEL	
PRODUCT DESCRIPTION	"Nagarjuna" super synthetic enamel is an alkyd paint with good gloss retention and resistance to exterior and interior weathering conditions.
RECOMMENDED USE	A finish coat on steel,wood,FRP substrates
PROPERTIES	
Finish	High gloss/semi-Gloss/Matt
Shade	Any shade as per IS: 5, R.A.L.
Standard Coverage	10-12 Sq.Mts/ltr
Specific Gravity	0.9-1.1 Kg/ltr
Flash point	30C
Touch Dry	3 hours
Surface Dry	8 hours
Hard Dry	24 hours
Scratch hardness(min)	1000 gms.
DFT	25 microns
APPLICATIONS SYSTEM	
Method of Application	Airless Spray/Air Spray/Brush
Compatible Thinner	"Nagarjuna" Synthetic Enamel Primer
Recoatible Interval	24 Hours
Packing	20 Lts
Storage Life	As Long as the containers are kept firmly Sealed, the contents can be stored up to 6 Months without deterioration
Specifications, and data given above represent test results obtained under controlled Conditions. These may vary under actual circumstance	

PRODUCT CODE: DIC/403



Plot No. 8A, Rasoolpura, Secunderabad - 500 003. A.P. India.

Tel : 040-27901196, Telefax : 040-27906871, E-mail : jnanadev@devindustrialcoatings.com