



DEV INDUSTRIAL COATINGS

(Manufacturers of Hi-Tech Industrial Paints)

(AN ISO 9001:2008 CERTIFIED COMPANY)

“NAGARJUNA”EPICOAT 2K-EPOXY PAINT	
PRODUCT DESCRIPTION	“Nagarjuna”Epicoat is a two component cold cured Epoxy which forms an extremely tough, high performance Coating. Epicoat possesses good flexibility and remarkable resistance to oils, chemicals, acids and alkalies
RECOMMENDED USE	Long lasting finish coat on a variety of substrates such as steel structures, pipelines, chemicals plants, machinery, oil tankers industrials floors etc.
PROPERTIES	
Finish	High Gloss/semi-gloss/matt
Shade	Any shade as per R.A.L & IS: 5.
Standard coverage	9-10sq.mts/ltr
Specific gravity	1.1-1.3 kg/ltr
Flash point	31C
Touch Dry	2 hours
Hard Dry	12 Hours
Scratch Hardness(matt)	2000 gms
DFT	25 microns
APPLICATION SYSTEM	
Mixing Ratio	Part A: Part B 3:1 by volume
Method of application	Airless spray/Air spray/Brush
Compatible Thinner	“Nagarjuna”Epoxy thinner.
Compatible Primer	“Nagarjuna” Epoxy Primer
Pot Life (min)	6hours
Recoatable Interval	24hours
Packing	20 Ltrs
Storage Life	As long as the material remains Unmixed and the containers are kept firmly sealed, the contents can be stored upto 6 months without deterioration
Specifications, and data given above represent test results obtained under controlled Conditions. These may vary under actual circumstance	

PRODUCT CODE: DIC/201



Plot No. 8A, Rasoolpura, Secunderabad - 500 003. A.P. India.

Tel : 040-27901196, Telefax : 040-27906871, E-mail : jnanadev@devindustrialcoatings.com