



DEV INDUSTRIAL COATINGS

(Manufacturers of Hi-Tech Industrial Paints)

(AN ISO 9001:2008 CERTIFIED COMPANY)

"NAGARJUNA" POLYCOAT PII 2K-POLYURETHANE PAINT	
PRODUCTION DESCRIPTION	"Nagarjuna" Polycoat PII is a two component polyurethane paint with very good colour retention and gloss, the coating is resistant to chemicals, water, petrol, mineral oils, marine corrosion and Industrial atmospheres. It has good impact and abrasion resistance Long lasting finish coat on a variety of substrates such as metal, wood FRP, Concrete etc.
RECOMMENDED USE	
PROPERTIES	
Finish	High Gloss/semi-gloss/matt
Shade	Any shade as per RAL, IS : 5.
Standard coverage	9-10 sq.Mts/lts
Specific Gravity	1.0-1.2Kg/ltr
Flash point	31C
Touch Dry	Less than 30minutes
Surface Dry	2 hours
Hard Dry	12 hours
Scratch Hardness(min)	2000 gms
DFT	25 microns
APPLICATIONS SYSTEM	
Mixing Ratio	Part A: Part B 3:1 by volume
Method of application	Airless Spray/Air spray/Brush
Compatible Thinner	"Nagarjuna" PU Part-C
Compatible primer	"Nagarjuna" 2K Polycoat Primer
Pot Life	6hours
Recoat interval	6hours
Packing	20Lts
Storage Life	As long As the material remains unmixed and the containers are kept firmly sealed, the contents can be stored upto 6 months without deterioration
Specifications, and data given above represent test results obtained under controlled Conditions. These may vary under actual circumstance	

PRODUCT CODE: DIC/102



Plot No. 8A, Rasoolpura, Secunderabad - 500 003. A.P. India.

Tel : 040-27901196, Telefax : 040-27906871, E-mail : jnanadev@devindustrialcoatings.com